


# S10HD 10" x 90" Industrial Horizontal Belt Sander

## Power. Precision. Throughput.

Built for continuous industrial use—flat, repeatable finishes on large parts.

#### **Operator Wins**

- Cover more area per pass with a wide 10" x 90" belt
- Rigid platen delivers true flats and consistent finishes
- ≈3500 SFPM for aggressive removal without sacrificing finish
- One-knob tracking + air tension (40–50 PSI) for quick changeovers
- Magnetic controls with jog; 24V operator-safe push-buttons



- Deburr laser/plasma/saw-cut parts
- Flatten plates and bar stock
- Blend welds; smooth parting lines
- Prep for coating or bonding





| Feature          | Details                    | Feature     | Details                             |
|------------------|----------------------------|-------------|-------------------------------------|
| Belt size        | 10" x 90"                  | Belt speed  | ≈ 3500 SFPM                         |
| Work surface     | 10" x 28"                  | Platen      | Steel, reversible, 10" x 29"        |
| Motor            | 10 HP, 3-phase             | Voltage     | 230V or 460V                        |
| FLC              | 24 A @ 230V; 12.5 A @ 460V | Controls    | Magnetic w/ jog; 24V                |
| Tracking/Tension | One-knob; air 40–50 PSI    | Dust        | 6" port hookup (external collector) |
| Ship dims        | 65"L x 65"W x 60"H*        | Ship weight | ≈ 1400 lb*                          |

**△ Dust Collection Notice:** This machine provides a 6" port hookup for a dust collection system only—no internal collector. Connect to your shop's external collector.

#### **Offer & Ordering**

• Free application review

### **Request a Quote Today**

• Call (269) 382-2050 or visit: kalamazooind.com

