

S8HD Series Belt Sanders Instruction Manual

www.kalamazooind.com

Kalamazoo Industries, Inc. 6856 East K Avenue Kalamazoo, MI 49048 Phone 269-382-2050

GENERAL POWER TOOL SAFETY WARNINGS



WARNING: TO REDUCE THE RISK OF FIRE OR SHOCK HAZARD, DO NOT EXPOSE THIS EQUIPMENT TO RAIN, LIQUID, OR MOISTURE.

READ AND SAVE ALL WARNINGS AND INSTRUCTIONS FOR FUTURE REFERENCE

PRECAUTIONS

- Always wear safety glasses when operating power tools.
- Keep work area clean and well lit.
- Do not operate power tools in explosive atmospheres, such as the presence of flammable liquids, gases or dust.
- Keep children and bystanders away while operating a power tool.
- Keep long hair tied back or covered and never wear loose fitting clothing near a running machine.
- Additional precautions may be necessary when grinding materials that are flammable or have other hazardous properties. Consult manufacturer of materials for safe grinding and handling.

OPERATING INSTRUCTIONS

- Disconnect power before making any adjustments
- Abrasive belt rotation is counterclockwise. If the abrasive belt is lap spliced, be sure of correct rotation. Butt spliced belts are bi-directional.

Belt Tensioning

- Belt tension is pre-set with air regulator (53). No belt tension adjustment is needed. Set air pressure to **40 PSI** for proper belt tension. **Do not exceed 50 PSI**.
 - Use the air valve (53) to apply or release belt tension.
 - Always release air pressure after daily use to reduce unnecessary belt stretching.

OPERATING INSTRUCTIONS – Continued

Belt Changing

- Turn the machine OFF.
- Release air pressure with the control valve—the upper pulley will retract to release tension.
- Open the guard door and remove the sanding belt.
- Install the new belt.
 - Check for directional arrows inside the belt and align correctly.
- Close the guard door securely.
- Reapply tension using the control valve.

Belt Tracking

- After applying belt tension, use the JOG switch and tracking knob to align the belt.
 - Multiple jogs may be needed to center the belt.
- While holding the JOG switch, adjust the tracking knob:
 - Turn clockwise → tilts pulley upward, moving the belt away from the machine frame.
 - Turn counter clockwise → tilts pulley downward, moving the belt toward the machine frame.
- Once the belt is properly tracked in JOG mode, switch to RUN mode.
 - Warning: Keep hands clear of the belt when powering on.

Note

- Examine the abrasive belt carefully before use. Never use an abrasive belt with a nicked or cut edge, crease, or handling damage.
- If using a dust collector, empty the base and check or replace the filter regularly to maintain performance and prevent combustible buildup.

WARRANTY: All products are guaranteed for a period of one year to the original purchaser, against defects in material workmanship under normal use. Exclusions may apply.

RETURN POLICY: Authorization must be obtained BEFORE returning merchandise. Contact our customer service department at 269-382-2050 for a return authorization number. Include with your return a copy of your invoice or packing slip. Materials must be sent back prepaid unless otherwise indicated. All returns will be subject to a 10% restocking charge. No returns will be accepted after one year of the invoice date.

BELT SANDER SAFETY:

- 1) Read the operating instructions before running machine.
- 2) Always wear safety glasses or a full-face shield for protection.
- 3) Keep hands clear of the sanding area.
- 4) Never wear gloves or loose-fitting clothing when operating this machine.
- 5) Always keep hair tied back or covered.
- 6) Let machine rotation come to a full stop before changing belt.
- 7) Keep Safety guards in place. Do not alter guards or machine in any way. Any alterations to guards or machine could cause serious injury.
- 8) All belt sanders should be operated in a well-ventilated area. The dust created when some materials are sanded can be harmful. Dust masks are recommended as practical means of minimizing dust inhalation. Fumes from other sources can also cause fires when in contact with sanding sparks.
- 9) Sparks created by sanding should be directed downward and away from the face and body. Do not grind near flammable material.
- 10) Electric sanding machines are not intended for use in or near water. This includes an operator standing on a wet floor or working around containers of water or other conductive liquids.

